

For Flex • AC • MCI cable. Zinc die-cast.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
L42	34200	3/8	1/2	50	500	.930	.403	1.155	.530-.620	.400
L420*	34021	3/8	1/2	50	500	.930	.403	1.155	.530-.620	.400 x .580
L421	34210	1/2	1/2	25	250	1.425	.405	1.420	.850-910	.620
L422	34220	3/4	3/4	25	250	1.555	.464	1.556	1.100-1.135	.820
L423	34230	1	1	10	100	1.740	.530	1.860	1.255-1.375	.940
L424	34240	1-1/4	1-1/4	5	50	1.982	.696	2.240	1.550-1.610	1.240
L425	34250	1-1/2	1-1/2	5	50	2.176	.659	2.615	1.810-1.895	1.460
L426	34260	2	2	5	30	2.550	.690	3.155	2.260-2.485	1.935
L427	34270	2-1/2	2-1/2	5	5	2.850	.855	3.753	2.770-2.950	2.440
L428	34280	3	3	1	6	3.870	.990	4.373	3.170-3.560	2.980
L429	34290	3-1/2	3-1/2	1	6	4.204	.956	4.894	3.630-4.155	3.478
L4210	34211	4	4	1	6	4.565	1.000	5.421	4.030-4.635	3.977



*L420 not listed for flexible metal conduit.
 Refer to page E-9 for MC cable connectors with our largest cable ranges.
 Refer to chart on page E-27 for list of cable types.
 Concrete tight when taped.



L42



L421



L427

