

## 90° SNAP-TITE® Connectors

Zinc die-cast. With steel spring clip. For aluminum and steel Flex • AC • HCF • AC90  
• MCI cable.

SNAP-TITE® and SNAP2IT® products have been tested and listed by UL in accordance with UL’s ground fault requirements. For additional information see page Index-8.  
(See page E-1 for ring removal instructions.)

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|
| 850ST          | 80154                    | 3/8        | 1/2     | 50       | 500     | 1.540 | .430  | 1.800 | .440-.750   |
| 850AST*        | 80156                    | 3/8        | 1/2     | 50       | 500     | 1.600 | .490  | 1.775 | .440-.750   |
| 851ST‡         | 80158                    | 1/2        | 1/2     | 25       | 250     | 1.600 | .430  | 2.140 | .642-1.075  |
| 851AST*‡       | 80160                    | 1/2        | 1/2     | 25       | 250     | 1.651 | .490  | 2.145 | .648-1.081  |



UL

us

E18304



SP

LR49636

MADE IN USA.

\*Provided with insulated throat. ‡Also for MCI-A cable. See page E-33 and E-34 for MCI-A cable ranges. Refer to chart on page E-30 for list of cable types. Concrete tight when taped.

