Arlington®



FB417S





FB417SLP Low Profile



FB417SLP



Nail On Fan & Fixture Boxes with Steel **Mounting Bracket**

Non-metallic box with steel mounting bracket for fast and easy nail on installation to a single or double joist.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
FB417S	72171	For up to 1-1/2" ceiling thickness (Including drywall on furring strips or hat channel) 20.0 cu. in.	25	25	4.563	3.500	4.279
FB417SLP	72199	For 1/2" to 5/8" ceiling thicknesses only 20.0 cu. in.	25	25	6.625	2.906	4.570
PATENTED. Refer to chart on page R-25 for load ratings and number of single conductors.							

Refer to chart on page R-25 for load ratings and number of single conductors.



FEATURES AND BENEFITS • No loose parts to misplace, totally self contained!

- FB417S features convenient indicator marks
- for 1/2", 5/8", and 3/4" ceiling thicknesses
- Works well on single or double wood joists • Fan/fixture installation screws are parked and
- ready for easy fan/fixture bracket installation!
- UL rated: 70 lb fan/fixture; CSA rated: 50 lb fan/fixture
- FB417SLP also works with wood and
- manufactured I-beams
- 2 hour fire rating

FAN/FIXTURE BOX INCLUDES

Non-metallic box with steel mounting bracket, installed NM cable connector, mud cover, second KO, two parked in place bracket nails, and two fan/fixture bracket installation screws (screwed in place until removed by installer).



INSTALLATION INSTRUCTIONS



Nails to the joist for a super secure installation! All photos shown with FB417S

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.



