

# **Extra Deep Fan & Fixture Mounting Box**

Our deepest L-shaped fan/fixture box mounts securely to single or double joists with a shipped in place center screw.

CATALOG	UPC/DCI/NAED	DESCRIPTION		STD	DIM	DIM	DIM
NUMBER	MFG #018997	/ CU. IN.		PKG	A	B	C
FB444	72187	For 1/2" or 5/8" drywall 25.6 cu. in.	25	25	5.330	4.000	4.716





PATENTED.

MADE IN USA.

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided. Refer to chart on page R-25 for load ratings and number of single conductors.

#### **FEATURES AND BENEFITS**

- Locator posts assure proper positioning of fan/fixture bracket
- Fan/fixture installation screws are parked, ready for easy fan/fixture bracket installation!
- UL rated: 70 lb fan, 200 lb fixture; CSA rated: 50 lb fan/fixture
- No loose parts to misplace, totally self contained!
- Arlington's deepest fan box!
- 2 hour fire rating
- Easy wire access

## **FAN/FIXTURE BOX INCLUDES**

A ready to tighten center screw, installed NM cable connector, mud cover, multiple KOs, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).



## **INSTALLATION INSTRUCTIONS**





- 1) Position box alongside joist. Tighten center screw, mounting box to joist.
- 2) Position mounting bracket over locator posts to assure proper position.
- 3) Remove captive bracket installation screws. Use them to mount fan/fixture bracket.

## OPTIONAL

If necessary the bottom of the box can be opened to access wires.

4) Pull wires through knockout. (Installation of drywall not shown.)







Locator posts for positioning of bracket installation screws





