

## Press-On Fan & Fixture Mounting Boxes

The fastest, easiest way to mount fans and fixtures. Ships ready-to-install!

### FEATURES AND BENEFITS

- No loose parts to misplace, totally self-contained!
- Gripping tangs press-hold to the joist while you reach for your screwdriver
- Comes with NM connector installed and mud cover in place
- Fan/fixture installation screws are parked...ready for easy fan/fixture bracket installation!
- FB426F's flanged design forms a protective barrier against air infiltration
- UL rated: 70 lb fan, 200 lb fixture; CSA rated: 50 lb fan/fixture
- 2-Hour Fire Rating

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
FB415	72167	For 1/2" or 5/8" drywall 10.3 cu. in.	25	25	2.250	.500	4.250
FB4150*	72182	For 1/2" or 5/8" drywall 10.3 cu. in.	100	100	2.250	.500	4.250
FB426	72179	For 1/2" or 5/8" drywall 16.0 cu. in.	25	25	2.625	.500	4.250



FB415



FB426



E170558 LR49636





Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.

\*Bulk packing for lower cost.

Refer to chart on page R-24 for load ratings and number of single conductors.


**PATENTED.**



### EACH FAN/FIXTURE BOX INCLUDES...

Press-on box with ready-to-tighten center screw, installed NM cable connector, mud cover, second KO, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).

### INSTALLATION INSTRUCTIONS (FB415)



1. Press box onto joist. Gripping tangs, hold the box in place temporarily.
2. Tighten center screw to secure to joist.
3. Push NM cable through connector.
4. Remove two long, "parked" screws for installation of bracket.
5. Use the screws to install fan/fixture bracket through the oval slots in the box, directly into the joist.