## **DROPIN®** Floor Box Kits



### FIVE MINUTE installation with SINGLE Hole Saw • Low Profile Covers



#### Fastest box installation!



 Determine box location, taking care to avoid structural framing members. Using hole saw cut 4-1/4" diameter opening through floor and subfloor.



2 Insert mounting bracket. Using indicator marks align bracket for proper receptacle orientation. Tighten (3) wing screws to secure bracket to floor.



Non-metallic Blank Covers



3 Pull cable. Install in box with supplied cable connector. Attach box to bracket with (3) #8 x 1/2" sheet metal screws (supplied) through the U-shaped cut outs in the box flange.



4 Wire receptacle. Install in box. Attach supplied gasket support plate to receptacle with #6 x 1/2" screw.



Cover Installation Install gasket. Attach metal or non-metallic blank cover to box with (3) #8 x 1/2" flathead machine screws. When using the in-use non-metallic cover, substitute the colored in-use plate for the black gasket support plate.





Arlington's LISTED **DROP IN**® Floor Box Kits are the fastest way to install a BOX nearly flush in an EXISTING floor.

#### Designed for flush, neat installations and TIME-SAVINGS these floor boxes install with a SINGLE hole saw and sit just 1/8" off the floor!

DROPIN box accommodates most 3.5" standard covers, but Arlington's round low profile covers seat flush into the non-metallic ring, reducing trip hazards.

BRASS OR NICKEL-PLATED BRASS
Metal Covers have
two gasketed flip lids
that keep water out
and protect the box.





DROPIN kits are also available with NON-METALLIC **Blank Covers**. They're perfect for covering unused receptacles. To use the receptacle simply remove the blank cover.

 Five decorator colors: dark brown, light almond, gray, caramel, black – each with a matching

non-metallic

mounting bracket, gasket and carpet ring.





1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com UPC/DCI/NAED

MFG. #018997

CATALOG

NUMBER

# Metal or Non-metallic Covers • FASTEST Installation in Existing Floor

UNIT

PKG

STD

PKG



DROP IN® BO	X KITS with ME	ETAL COVERS		
FLB4360MB 00760		Round non-metallic box, Brass cover w flip lids	1	1
FLB4360NL	00761	Round non-metallic box, NIckel-plated Brass cover w flip lids	1	1
ADD SUFFIX 'GC	' to order with G	round Clip (Canada)		
non-metallic gas	ket support plat	DROP IN BOX Kits include non-metallic box, round 4" diameter te, gasket, carpet ring, UL Listed 15 amp TR duplex receptacle, m lathead screws and (1) #6 x 1/2" screw.		

DESCRIPTION

FINISH, COVER STYLE

FLB4360MB

brass cover





nickel-plated brass cover

	UPC/DCI/NAED MFG. #018997	DESCRIPTION	COLOR STYLE / COLOR	UNIT PKG	STD PKG	
DROPIN® BO	X KITS with NON-	METALLIC BLANK COVERS				0 0 0 0 0
FLB4360BR	00763	Round non-metallic box	Blank, Dark Brown	1	1	COVERS, CARPET RINGS, GAS IN 5 COLORS
FLB4360LA	00766	Round non-metallic box	Blank, Light Almond	1	1	IN 3 COLORS
FLB4360GY	00765	Round non-metallic box	Blank, Gray	1	1	
FLB4360CA	00764	Round non-metallic box	Blank, Caramel	1	1	
FLB4360BL	00762	Round non-metallic box	Blank, Black	1	1	

ADD SUFFIX 'GC' to order with Ground Clip (Canada)

DROP IN BOX Kits with BLANK NON-METALLIC COVERS include non-metallic box, round 4" diameter non-metallic cover blank, non-metallic gasket support plate, gasket, carpet ring, UL Listed 15 amp TR duplex receptacle, mounting bracket, NM94 and NM95 cable connectors, (3) #8 x 1/2" flathead screws and (1) #6 x 1/2" screw.



www.aifittings.com

Patent pending FLB4360 0716 REV0916/15M