# Non-Metallic Liquid-Tight Connectors

NEW!

## *Screw-on Straight and 90° Connectors for Liquid-Tight Conduit*

Designed for use with non-metallic liquid-tight conduit Type B, Arlington's non-metallic connectors are produced from UV rated plastic for long outdoor life.

**Easy, Screw-on Installation**

Arlington's liquid-tight connectors ship fully assembled and ready to install on conduit. There's no disassembly required. Simply loosen the nut, insert conduit and retighten the nut for a secure, liquid-tight seal.

- Removable, reusable
- **Non-metallic** Straight and 90° in seven trade sizes for non-metallic liquid-tight conduit, type B
- cULus Listed

## Non-Metallic Screw-on Liquid Tight Connectors

| CATALOG NUMBER | UPC/DCI/NAED MFG. #018997 | TRADE SIZE | DIMENSIONS (INCHES) A | B | C | UNIT PKG | STD PKG |
|---|---|---|---|---|---|---|---|
| **STRAIGHT** | | | | | | | |
| **NMLT3C** | 34300 | 3/8" | 2.052 | .567 | 1.371 | 25 | 100 |
| **NMLT5C** | 34301 | 1/2" | 2.121 | .553 | 1.360 | 25 | 100 |
| **NMLT7C** | 34302 | 3/4" | 2.232 | .630 | 1.560 | 10 | 100 |
| **NMLT10C** | 34303 | 1" | 2.410 | .719 | 1.829 | 5 | 50 |
| **NMLT12C** | 34304 | 1-1/4" | 2.456 | .771 | 2.400 | 5 | 50 |
| **NMLT15C** | 34305 | 1-1/2" | 2.712 | .780 | 2.650 | 5 | 50 |
| **NMLT20C** | 34306 | 2" | 3.070 | .880 | 3.230 | 2 | 20 |
| **90 DEGREE** | | | | | | | |
| **NMLT903C** | 34307 | 3/8" | 1.955 | .500 | 3.117 | 25 | 100 |
| **NMLT905C** | 34308 | 1/2" | 1.955 | .500 | 3.196 | 10 | 100 |
| **NMLT907C** | 34309 | 3/4" | 2.220 | .537 | 3.685 | 10 | 100 |
| **NMLT9010C** | 34310 | 1" | 2.813 | .719 | 4.125 | 5 | 50 |
| **NMLT9012C** | 34311 | 1-1/4" | 4.125 | .765 | 4.750 | 2 | 20 |
| **NMLT9015C** | 34312 | 1-1/2" | 4.313 | .810 | 5.063 | 2 | 20 |
| **NMLT9020C** | 34313 | 2" | 5.188 | .860 | 5.875 | 1 | 10 |








**Arlington®**

1 Stauffer Industrial Park
Scranton, PA 18517
**800/233.4717 • Fax 570/562.0646**
**www.aifittings.com**



© 2021 Arlington Industries, Inc. 1221/15M