IN BOX® COVER KIT for Concrete Floor Box



Recessed Cover Kit with Decorator-style Receptacle





INSTALLATION INSTRUCTIONS



After concrete has cured and finished floor installed, cut the installed FLBC4500 concrete box to finished floor height. If using the low voltage divider, cut the same amount from the bottom of the divider as you removed from the can.



2 Secure the leveling ring assembly to the installed FLBC4500 can with PVC cement.



3 Install the blank cover in unused boxes to avoid possible trip hazard.

Arlington's new IN BOX® COVER KITS give installers the best way to install a receptacle in new concrete.

These new COVER KITS are **RECESSED** and install into the can so they look great! And they reduce the trip hazard caused by plugs sticking out of the box.

You can also have power and low voltage in the same box. Talk about convenience!

IN BOX Cover Kits are available with metal flanges in brass or nickel-plated brass. And plastic, in five colors: light almond, gray, caramel, black and brown.

They're easy to install into our FLBC4500 concrete floor box (sold separately).

Made of heavy-duty plastic, the 4.5" non-metallic FLBC4500 concrete box is a common size, that accommodates our new IN BOX COVER and other common

single-door, 4" diameter. 3-hole covers.





4 Remove blank cover to use receptacle.



5 Install the slotted in-use plug cover and store blank cover for future use.

Available with blank metal or plastic covers in a variety of colors.





1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com




Put a RECESSED Receptacle in New Concrete – The Easy Way!



KITS INCLUDE

Leveling Ring Assembly (w/ Carpet Flange, Funnel & UL Listed 15 A Decorator Receptacle), Low Voltage Divider, Blank Cover w/ Gasket, In-Use Slotted Cover, Low-Voltage Plug, #8 x 5/8" Lg. Flat Head Screw



	CATALOG NUMBER	UPC/DCI/NAED MFG. #018997	DESCRIPTION FINISH/COLOR, COVER STYLE	UNIT PKG	STD PKG
	FLBC4500	22010	4.5" Non-metallic ROUND BOX for Concrete Pours (conduit plugs, mud cover)	1	5
			AL FLANGE, BLANK AND IN-USE SLOTTED PLUG COVER		
	FLBC4560DM	IB 09105	RECESSED COVER KIT – Brass, w/ Decorator Style Receptacle	1	1
	FLBC4560DN	L 09106	RECESSED COVER KIT – Nickel plated Brass, w/ Decorator Style Receptacle	1	1
IN BOX® COVER KIT WITH PLASTIC FLANGE, BLANK AND IN-USE SLOTTED PLUG COVER					
	FLBC4560DB	L 09100	RECESSED COVER KIT – Black, w/ Black Decorator Style Receptacle	1	1
	FLBC4560DB	R 09101	RECESSED COVER KIT – Dark Brown, w/ Dark Brown Decorator Style Receptacle	1	1
	FLBC4560DC	A 09102	RECESSED COVER KIT – Caramel, w/ Dark Brown Decorator Style Receptacle	1	1
	FLBC4560DG	Y 09103	RECESSED COVER KIT – Gray, w/ Black Decorator Style Receptade	1	1
	FLBC4560DL	A 09104	RECESSED COVER KIT – Light Almond, w/ Light Almond Decorator Style Receptacle	1	1

Slotted In-Use Non-Metallic Non-Metallic Plug Cover Blank Cover

FLBC4560DBL

Black Cover

Slotted In-Use

Metallic Plug Cover

US



FLBC4560DBR Dark Brown Cover



Caramel Cover



FLBC4560DGY

Gray Cover



FLBC4560DCA Light Almond Cover



Blank Metal

Cover







FLBC4560DNL Nickel Plated Metal Cover

NOTE: Receptacle ships installed in the leveling ring assembly in all kits

© 2016 Arlington Industries, Inc.

1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com

Distributed by